

# **HHL-FLOMAX** PUMPS

## **FOR MARINE INDUSTRY**



- Auxiliary Fire Control

46 CFR Compliant



We don't just go with the flow, we create it!

 **MP PUMPS, INC.**

[www.mppumps.com](http://www.mppumps.com)

# HHL-FLOMAX

## Self Priming Centrifugal Pump

HHL-FLOMAX "HR" high pressure self-priming pumps meet USCG specifications for auxiliary fire control.

The high suction centerline and impeller design eliminates premature priming loss while ensuring consistent priming capability. The HHL-FLOMAX pump is capable of achieving up to 25 feet suction lift.

The volute and impeller are removable and easily replaced.



### HHL-FLOMAX FEATURES

- **Suction and Discharge:** 1 1/2" x 1 1/2" NPT  
2" x 2" NPT
- **Flows:** To 140 GPM
- **Pressures:** To 190 TDH
- **Housing:** Cast Iron Class 30 or Silicon Bronze CA 875
- **Volute:** Cast Iron Class 30 or Silicon Bronze CA 875
- **Impeller:** Cast Iron Class 30 or Silicon Bronze CA 875
- **Adapter:** Cast Iron Class 30 or Silicon Bronze CA 875
- **Drive Sleeve:** 304 Stainless Steel
- **Seal, Type 21:** Carbon/Ceramic/Viton  
Optional Seals Available
- **Fasteners:** Stainless Steel
- **Mounting Options:** Close Cpld to 182/184 TC Motor Frame  
Pumpak  
Engine Drive  
Pedestal  
Hydraulic Drive

### Additional Marine Pumps Available:

#### **FLOMAX** • Self Priming



#### **CHEMFLO** • Nickel/Bronze/Aluminum



#### **FRX 75-SP** • Self Priming • Marine Ignition Protected Motors • Hydraulic Driven

