

FRX 75-SP **FRX** 75-SP Hydraulic Pump

FOR MARINE INDUSTRY



- Marine Air Conditioning
- Marine Refrigeration
- Washdown
- Hydraulic Cooling
- Bait Tank



- ISO 8846 Marine Ignition Proof

We don't just go with the flow, we create it!®



34800 BENNETT • FRASER, MI 48026-1686
(586) 293-8240 • FAX (586) 293-8469
(800) 563-8006 • www.mppumps.com

FRX 75-SP

FRX 75-SP Hydraulic Pump

Centrifugal Pump

Model FRX 75-SP is a high performance self-priming 316 stainless steel centrifugal pump. The pump is ideal for marine, industrial, agricultural or commercial applications where suction lift is required.

The FRX 75-SP model features all 316 stainless steel components for superior corrosion resistance when pumping chemical compounds. A carbon/ceramic/viton bellows shaft seal is standard. Ports are 3/4" NPT with 1/8" NPT fill port. The O-ring/flapper design enhances the self-priming capability to 12 foot suction lift. Marine ignition protected motors available.



Patent Pending

FRX 75-SP FEATURES

- Housing: 316 Stainless Steel (Investment Cast)
- Cover: 316 Stainless Steel (Investment Cast)
- Impeller: 316 Stainless Steel Semi-Open (Sintered PM)
- Wear Plate: 316 Stainless Steel
- Mechanical Seal: Carbon/Ceramic/Viton Bellows 150 PSI Special Seals Upon Request
- O-ring/Flapper: Viton
- Motor: 12V DC and 24V DC
115V AC ODP and TENV
230V AC TENV
- Weights: Pump W/AC Motor 18 lbs.
Pump W/DC Motor 12 lbs.
- Port Sizes: 3/4" NPT
1/8" NPT Fill Port
- Hydraulic Motor: .08 Cubic Inch Displacement
Max. Oil Flow - 3 GPM
Max Pressure - 1000 PSI
- Hydraulic Port Sizes: SAE #4 Pressure
SAE #6 Tank

Additional Marine Pumps Available:

FLOMAX

- Self Priming



HHL-FLOMAX

- ABS Type Approved



CHEMFLO

- Nickel/Bronze/Aluminum



34800 BENNETT • FRASER, MI 48026-1686
(586) 293-8240 • FAX (586) 293-8469
(800) 563-8006 • www.mppumps.com